

SA Rod end DSSAL5-T-K-DURBAL - DSSAL5-T-K-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/sa/dssal5-t-k-durbal>

DSSAL5-T-K



male thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

rod end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]			
DSSAL 5 T/K	5		M 5	B 8	C1 6,00	d2 18

type	measurement [mm]		h	alpha [°]	load rating C0 [kN]	weight [kg]
	l1 min	l2 min				
DSSA / DSSAL 5 T/K	19		33	13	6,0	0,013

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952490564
Inside diameter	5 mm
Inside diameter	0.197" inch
Outside diameter	18 mm
Outside diameter	0.709" inch
Thickness	8 mm
Thickness	0.315" inch
Type	SA
Weight	13 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE