

## SA Rod end SSA6-T-K-DURBAL - SSA6-T-K-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/sa/ssa6-t-k-durbal>

### SSA6-T-K



**male thread:** maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

**rod end body:** stainless steel

**Sliding combination:** steel / bronze-PTFE composite

**inner ring:** stainless steel, hardened and ground

**Outer ring:** stainless steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** maintenance free

order number	right hand thread	left hand thread	measurement [mm]				
SSA 6 T/K	6	M 6	9	6,75	20		

type	measurement [mm]			load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	l <sub>2</sub> min	h		
SSA / SSAL 6 T/K	21	36	13	7,7	0,020

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952490595
Inside diameter	6 mm
Outside diameter	20 mm
Thickness	9 mm
Type	SA
Weight	20 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE