

## SA Rod end SSA12-T-K-DURBAL - SSA12-T-K-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/sa/ssa12-t-k-durbal>

### SSA12-T-K



**male thread:** maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

**rod end body:** stainless steel

**Sliding combination:** steel / bronze-PTFE composite

**inner ring:** stainless steel, hardened and ground

**Outer ring:** stainless steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** maintenance free

order number	d	G	B	C1	d2
SSA 12 T/K	12	M 12	16	12,00	32

type	measurement [mm]		h	alpha [°]	load rating C0 [kN]	weight [kg]
	l1 min	l2 min				
SSA / SSA12 T/K	32	54	13		24,0	0,085

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952490700
Inside diameter	12 mm
Outside diameter	32 mm
Thickness	16 mm
Type	SA
Weight	85 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE