

SA Rod end

SSA16-T-K-DURBAL - SSA16-T-K-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/sa/ssa16-t-k-durbal>

SSA16-T-K



male thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

rod end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]			
SSA 16 T/K	16		M 16	21	15,00	42

type	measurement [mm]		h	alpha [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂ min				
SSA / SSAL 16 T/K	37	21	66	15	39,0	0,210

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952490786
Inside diameter	16 mm
Inside diameter	0.63" inch
Outside diameter	42 mm
Outside diameter	1.654" inch
Thickness	21 mm
Thickness	0.827" inch
Type	SA
Weight	210 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE