

SA Rod end SSAL20-T-K-DURBAL - SSAL20-T-K-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/sa/ssal20-t-k-durbal>

SSAL20-T-K



male thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

rod end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]			
SSAL 20 T/K	20		G	B	C1	d2
			M 20 x 1,5	25	18,00	50

type	measurement [mm]			alpha [°]	load rating C0 [kN]	weight [kg]
	l1 min	l2 min	h			
SSA / SSAL 20 T/K	45	25	78	14	57,0	0,380

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952490878
Inside diameter	20 mm
Inside diameter	0.787" inch
Outside diameter	50 mm
Outside diameter	1.969" inch
Thickness	25 mm
Thickness	0.984" inch
Type	SA
Weight	380 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE