

## SA Rod end SSAL25-T-K-DURBAL - SSAL25-T-K-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/sa/ssal25-t-k-durbal>

### SSAL25-T-K



**male thread:** maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

**rod end body:** stainless steel

**Sliding combination:** steel / bronze-PTFE composite

**inner ring:** stainless steel, hardened and ground

**Outer ring:** stainless steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** maintenance free

order number	d	G	B	C1	d2
SSAL 25 T/K	25	M 24 x 2	31	22,00	60

type	measurement [mm]			alpha [°]	load rating C0 [kN]	weight [kg]
	l1 min	l2 min	h			
SSA / SSAL 25 T/K	55	30	94	15	85,0	0,640

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952490953
Inside diameter	25 mm
Inside diameter	0.984" inch
Outside diameter	60 mm
Outside diameter	2.362" inch
Thickness	31 mm
Thickness	1.22" inch
Type	SA
Weight	640 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE