

SA Rod end SSA28-T-K-DURBAL - SSA28-T-K-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/sa/ssa28-t-k-durbal>

SSA28-T-K



male thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

rod end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	measurement [mm]	
right hand thread	left hand thread	
SSA 28 T/K	28	M 27 x 2
		B 35
		C1 24,00
		d2 66

type	measurement [mm]			load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂ min	h		
SSA / SSAL 28 T/K	62	33	103	107,0	0,800

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952490991
Inside diameter	28 mm
Inside diameter	1.102" inch
Outside diameter	66 mm
Outside diameter	2.598" inch
Thickness	35 mm
Thickness	1.378" inch
Type	SA
Weight	800 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE