

## SI Rod end DSSI6-T-K-DURBAL - DSSI6-T-K-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/si/dssi6-t-k-durbal>

### DSSI6-T-K



**female thread:** maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

**Rod end body:** stainless steel

**Sliding combination:** steel / bronze-PTFE composite

**Inner ring:** stainless steel, hardened and ground

**Outer ring:** stainless steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** maintenance free

order number	right hand thread	left hand thread	measurement [mm]							
DSSI 6 T/K			d	G	B	C1	d1	d2	d3	d4
			6	M 6	9	6,75	20	10,0	13	

type	measurement [mm]				load rating C <sub>0</sub> [kg]	weight [g]
	l <sub>1</sub> min	W	h	α		
DSSI / DSSIL 6 T/K	12	11	30	13	7,7	0,022

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952491127
Inside diameter	6 mm
Inside diameter	0.236" inch
Outside diameter	20 mm
Outside diameter	0.787" inch
Thickness	9 mm
Thickness	0.354" inch
Type	SI
Weight	22 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE