

## SI Rod end DSSIL8-T-K-DURBAL - SSIL8-T-K-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/si/ssil8-t-k-durbal>

### DSSIL8-T-K



**female thread:** maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

**Rod end body:** stainless steel

**Sliding combination:** steel / bronze-PTFE composite

**Inner ring:** stainless steel, hardened and ground

**Outer ring:** stainless steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** maintenance free

| order number | right hand thread | left hand thread | measurement [mm] |     |    |                |                |                |                |                |
|--------------|-------------------|------------------|------------------|-----|----|----------------|----------------|----------------|----------------|----------------|
| DSSIL 8 T/K  |                   |                  | d                | G   | B  | C <sub>1</sub> | d <sub>1</sub> | d <sub>2</sub> | d <sub>3</sub> | d <sub>4</sub> |
|              |                   |                  | 8                | M 8 | 12 | 9,00           | 24             | 12,5           | 16             |                |

| type                | measurement [mm]   |    |    | α  | load rating C <sub>0</sub> [kN] | weight [kg] |
|---------------------|--------------------|----|----|----|---------------------------------|-------------|
|                     | l <sub>1</sub> min | W  | h  |    |                                 |             |
| DSSIL / DSSIL 8 T/K | 16                 | 14 | 36 | 14 | 12,5                            | 0,047       |

## PRODUCT FEATURES

|                  |                  |
|------------------|------------------|
| Brand            | DURBAL           |
| N° Ean13         | 3663952491165    |
| Inside diameter  | 8 mm             |
| Outside diameter | 24 mm            |
| Thickness        | 12 mm            |
| Type             | SI               |
| Weight           | 47 g             |
| Thread           | Left-hand thread |
| Lubrication      | without          |
| Packaging        | 1                |

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE