

SI Rod end SSI22-T-K-DURBAL - SSI22-T-K-DURBAL

https://www.123bearing.com/bearing-housing/rod-end/si/ssi22-t-k-durbal

SSI22-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Rod end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]							
SSI 22 T/K			d	G	B	C1	d1	d2	d3	d4
			22	M 22 x 1,5	28	20,00	54	30,0	38	

type	measurement [mm]				load rating C ₀ (kg)	weight [kg]
	l ₁ min	W	h	α [°]		
SSI / SSI 22 T/K	37	32	84	15	68,0	0,540

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952491608
Inside diameter	22 mm
Inside diameter	0.866" inch
Outside diameter	54 mm
Outside diameter	2.126" inch
Thickness	28 mm
Thickness	1.102" inch
Type	SI
Weight	540 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE