

## SI Rod end SSIL30-T-K-DURBAL - SSIL30-T-K-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/si/ssil30-t-k-durbal>

### SSIL30-T-K



**female thread:** maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

**Rod end body:** stainless steel

**Sliding combination:** steel / bronze-PTFE composite

**Inner ring:** stainless steel, hardened and ground

**Outer ring:** stainless steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** maintenance free

order number	right hand thread	left hand thread	measurement [mm]							
SSIL 30 T/K			d	G	B	C <sub>1</sub>	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
			30	M 30 x 2	37	25,00	70	40,0	50	

type	measurement [mm]				load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	W	h	α [°]		
SSI / SSIL 30 T/K	51	41	110	17	114,0	1,100

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952491721
Inside diameter	30 mm
Outside diameter	70 mm
Thickness	37 mm
Type	SI
Weight	1100 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE