

SI Rod end

DSIL12-PK-DURBAL - DSIL12-PK-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/si/dsil12-pk-durbal>

DSIL12-PK



female thread; maintenance free, according to DIN ISO 12240-4, series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.

End end body: surface case plated

Sliding combination: steel / bronze-PTFE composite

Inner ring: bearing steel hardened and ground

Outer ring: rod end body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	d	G	B	C1	d1	d2	d3	d4
DSIL 12 PK	12	M 12	16	12,00	33	17,5	22	

type	l1 min	W	h	α [°]	load rating C0 [kN]	weight [kg]
DSI / DSIL 12 PK	22	19	50	13	24,00	0,100

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952491974
Inside diameter	12 mm
Inside diameter	0.472" inch
Outside diameter	33 mm
Outside diameter	1.299" inch
Thickness	16 mm
Thickness	0.63" inch
Type	SI
Weight	100 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE