

SA Rod end DSAL5-BK-DURBAL - DSAL5-BK-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/sa/dsal5-bk-durbal>

DSAL5-BK



male thread: maintenance free, according to DIN ISO 12240-4, series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.

rod end body: surface zinc plated

sliding combination: steel / bronze-PTFE composite

inner ring: bearing steel hardened and ground

Outer ring: rod end body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
DSAL 5 BK		5	M 5	8	6,0	19

type	measurement [mm]		α [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	h			
DSA / DSAL 5 BK	20	33	12	6,00	0,014

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952492353
Inside diameter	5 mm
Inside diameter	0.197" inch
Outside diameter	19 mm
Outside diameter	0.748" inch
Thickness	8 mm
Thickness	0.315" inch
Type	SA
Weight	14 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE