

SA Rod end SAL12-BK-DURBAL - SAL12-BK-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/sa/sal12-bk-durbal>

SAL12-BK



male thread: maintenance free, according to DIN ISO 12240-4, series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.

Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE composite

Inner ring: bearing steel hardened and ground

Outer ring: rod end body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
SAL 12 BK		12	M 12	16	12,0	33

type	measurement [mm]		α [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	h			
SA / SAL 12 BK	33	54	13	24,00	0,085

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952492506
Inside diameter	12 mm
Inside diameter	0.472" inch
Outside diameter	33 mm
Outside diameter	1.299" inch
Thickness	16 mm
Thickness	0.63" inch
Type	SA
Weight	85 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE