

## SA Rod end SA20-BK-DURBAL - SA20-BK-DURBAL


<https://www.123bearing.com/bearing-housing/rod-end/sa/sa20-bk-durbal>

### SA20-BK



male thread;  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.



Rod end body:

surface zinc plated

Sliding combination:

steel / bronze-PTFE composite

Inner ring:

bearing steel hardened and ground

Outer ring:

rod end body pressed around, outer race lined with bronze-PTFE composite

Lubrication:

maintenance free

order number	measurement [mm]		measurement [mm]				
	right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>
SA 20 BK			20	M 20 x 1,5	25	18,0	51

type	measurement [mm]		alpha [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	h			
SA / SA 20 BK	47	78	14	57,00	0,380

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952492650
Inside diameter	20 mm
Outside diameter	51 mm
Thickness	25 mm
Type	SA
Weight	380 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE