

SA Rod end SAL22-BK-DURBAL - DSAL22-BK-DURBAL


https://www.123bearing.com/bearing-housing/rod-end/sa/dsal22-bk-durbal

SAL22-BK



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.



rod end body:
surface zinc plated
sliding combination:
steel / bronze-PTFE composite
inner ring:
bearing steel hardened and ground
Outer ring:
rod end pressed around, outer race
lined with bronze-PTFE composite
Lubrication:
maintenance free

| order number | measurement [mm] | | measurement [mm] | | | | |
|--------------|-------------------|------------------|------------------|----|------|----|----|
| | right hand thread | left hand thread | d | G | B | C1 | d2 |
| SAL 22 BK | 22 | M 22 x 1,5 | 22 | 28 | 20,0 | 55 | |

| type | measurement [mm] | | alpha [°] | load rating C0 [kN] | weight [kg] |
|----------------|------------------|----|-----------|------------------------|----------------|
| | l1 min | h | | | |
| SA / SAL 22 BK | 50 | 84 | 15 | 68,00 | 0,480 |

PRODUCT FEATURES

| | |
|------------------|------------------|
| Brand | DURBAL |
| N° Ean13 | 3663952492698 |
| Inside diameter | 22 mm |
| Outside diameter | 55 mm |
| Thickness | 28 mm |
| Type | SA |
| Weight | 480 g |
| Thread | Left-hand thread |
| Lubrication | without |
| Packaging | 1 |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE