

SA Rod end SA22-BK-DURBAL - SA22-BK-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/sa/sa22-bk-durbal>

SA22-BK



male thread: maintenance free, according to DIN ISO 12240-4, series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.

rod end body: surface zinc plated

sliding combination: steel / bronze-PTFE composite

inner ring: bearing steel hardened and ground

Outer ring: rod end body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	measurement [mm]	
	right hand thread	left hand thread
SA 22 BK	22	M 22 x 1,5

type	measurement [mm]		α [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	h			
SA / SA 22 BK	50	84	15	68,00	0,480

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952492704
Inside diameter	22 mm
Outside diameter	55 mm
Thickness	28 mm
Type	SA
Weight	480 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE