

SA Rod end SA25-BK-DURBAL - DSA25-BK-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/sa/dsa25-bk-durbal>

SA25-BK



male thread: maintenance free, according to DIN ISO 12240-4, series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.

rod end body: surface zinc plated

sliding combination: steel / bronze-PTFE composite

inner ring: bearing steel hardened and ground

Outer ring: rod end body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
SA 25 BK		25	M 24 x 2	31	22,0	61

type	measurement [mm]		α [°]	load rating C ₀ [kN]	weight [kg]
	l ₂ min	h			
SA / SAL 25 BK	57	94	15	85,00	0,640

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952492735
Inside diameter	25 mm
Outside diameter	61 mm
Thickness	31 mm
Type	SA
Weight	640 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE