

SA Rod end SA25-BK-DURBAL - SA25-BK-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/sa/sa25-bk-durbal>

SA25-BK



male thread: maintenance free, according to DIN ISO 12240-4, series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.

Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE composite

Inner ring: bearing steel hardened and ground

Outer ring: rod end body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	measurement [mm]	
	right hand thread	left hand thread
SA 25 BK	25	M 24 x 2

type	measurement [mm]		α [°]	load rating C ₀ [kN]	weight [g]
	l ₁ min	h			
SA / SA 25 BK	57	94	15	85,00	0,640

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952492735
Inside diameter	25 mm
Inside diameter	0.984" inch
Outside diameter	61 mm
Outside diameter	2.402" inch
Thickness	31 mm
Thickness	1.22" inch
Type	SA
Weight	640 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE