

SA Rod end GAL8-UK-DURBAL - DGAL8-UK-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/sa/dgal8-uk-durbal>

GAL8-UK



male thread:
maintenance free,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.


rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body ground around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



| order number | | measurement (mm) | | | | | |
|-------------------|------------------|------------------|-----|-----------|---------------------------|----------------|--|
| right hand thread | left hand thread | d | G | B | C1 | d2 | |
| | GAL 8 UK | 8 | M 8 | 8 | 6,0 | 24 | |
| type | l1, min | l2, min | h | alpha [°] | load rating C0 [kN] | weight [kg] | |
| GAR / GAL 8 UK | 22 | 14 | 42 | 15 | 12,9 | 0,029 | |

PRODUCT FEATURES

| | |
|------------------|------------------|
| Brand | DURBAL |
| N° Ean13 | 3663952492810 |
| Inside diameter | 8 mm |
| Inside diameter | 0.315" inch |
| Outside diameter | 24 mm |
| Outside diameter | 0.945" inch |
| Thickness | 8 mm |
| Thickness | 0.315" inch |
| Type | SA |
| Weight | 29 g |
| Thread | Left-hand thread |
| Lubrication | without |
| Packaging | 1 |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE