

SA Rod end GAR25-UK-2RS-DURBAL - GAR25-UK-2RS-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/sa/gar25-uk-2rs-durbal>

GAR25-UK-2RS



male thread:
maintenance free,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGEAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.

Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free

order number	d	G	S	C1	d2
right hand thread left hand thread GAR 25 UK (-2RS)	25	M 24 x 2	20	17,0	64

type	measurement [mm]		h	α [°]	load rating C_0 [kN]	weight [kg]
	l_1 min	l_2 min				
GAR / GAL 25 UK-2RS	53	32	94	7	83,0	0,560

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952493176
Inside diameter	25 mm
Outside diameter	64 mm
Thickness	20 mm
Type	SA
Weight	560 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE