

# SA Rod end GAR30-UK-2RS-DURBAL - DGAR30-UK-2RS-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/sa/dgar30-uk-2rs-durbal>


## GAR30-UK-2RS



**male thread:**  
maintenance free,  
according to  
DIN ISO 12240-4,  
series E



**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.



**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / bronze-PTFE fabric

**Inner ring:**  
bearing steel, hardened, ground and  
spherical surface chromium plated

**Outer ring:**  
steel body ground around, outer race  
lined with bronze-PTFE composite

**Lubrication:**  
no lubrication necessary,  
maintenance free

order number	measurement [mm]	
right hand thread	d	g
left hand thread	s	C1
<b>GAR 30 UK (-2RS)</b>	30	M 30 x 2
	22	19,0
		73

type	measurement [mm]		h	alpha [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l, min	l <sub>1</sub> min				
GAR / GAL 30 UK-2RS	65	37	110	6	110,0	0,890

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952493220
Inside diameter	30 mm
Inside diameter	1.181" inch
Outside diameter	73 mm
Outside diameter	2.874" inch
Thickness	22 mm
Thickness	0.866" inch
Type	SA
Weight	897 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE