

GE Rod end GAR50-UK-2RS-DURBAL - DGAR50-UK-2RS-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/ge/dgar50-uk-2rs-durbal>

GAR50-UK-2RS



male thread: maintenance free, according to DIN ISO 12240-4, series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.

Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE fabric

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: steel body ground around, outer race lined with bronze-PTFE composite

Lubrication: no lubrication necessary, maintenance free

order number	d	G	S	C1	d2
GAR 50 UK-2RS	50	M 45 x 3	35	30,0	112

type	measurement [mm]		h	alpha [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂ min				
GAR / GAL 50 UK-2RS	107	60	185	6	290,0	3,400

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3616060467737
Inside diameter	50 mm
Outside diameter	112 mm
Thickness	35 mm
Type	GE
Weight	3400 g
Thread	Right-hand thread
Lubrication	without
Packaging	1
Standard	No standard

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE