

# SA Rod end GAR70-UK-2RS-DURBAL - GAR70-UK-2RS-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/sa/gar70-uk-2rs-durbal>


## GAR70-UK-2RS



male thread;  
maintenance free,  
according to  
DIN ISO 12240-4,  
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.



Rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE fabric

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
steel body ground around, outer race  
lined with bronze-PTFE composite

Lubrication:  
no lubrication necessary,  
maintenance free

order number	measurement (mm)	
right hand thread	left hand thread	
<b>GAR 70 UK-2RS</b>	70	M 56 x 4
	49	42,0
	160	

type	measurement [mm]		h	$\alpha$ [°]	load rating $C_0$ [kN]	weight [kg]
	l <sub>1</sub> min	l <sub>2</sub> min				
GAR / GAL 70 UK-2RS	125	87	235	6	610,0	8,200

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952493497
Inside diameter	70 mm
Outside diameter	160 mm
Thickness	49 mm
Type	SA
Weight	8200 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE