

## SI Rod end GIL10-UK-DURBAL - GIL10-UK-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/si/gil10-uk-durbal>

### GIL10-UK



**female thread:** maintenance free, according to DIN ISO 12240-4; series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.

**Sliding combination:** steel / bronze-PTFE fabric

**Rod end body:** surface zinc plated

**Inner ring:** bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:** steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** no lubrication necessary, maintenance free

order number	d	G	B	measurement [mm]	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
GIL 10 UK	10	M 10	9	7,0	29	15,0	19

type	measurement [mm]			$\alpha$ [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>3</sub> min	h	W			
GIR / GIL 10 UK	20	43	17	12	17,6	0,061

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952493657
Inside diameter	10 mm
Inside diameter	0.394" inch
Outside diameter	29 mm
Outside diameter	1.142" inch
Thickness	9 mm
Thickness	0.354" inch
Type	SI
Weight	61 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE