

## SI Rod end GIR12-UK-DURBAL - GIR12-UK-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/si/gir12-uk-durbal>

### GIR12-UK



**female thread:** maintenance free, according to DIN ISO 12240-4; series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.

**Sliding combination:** steel / bronze-PTFE fabric

**Inner ring:** bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:** steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** no lubrication necessary, maintenance free

order number	d	G	B	measurement [mm]	C <sub>1</sub>	C <sub>2</sub>	d <sub>2</sub>	d <sub>4</sub>
GIR 12 UK	12	M 12	10	8,0	34	17,5	22	

type	measurement [mm]			$\alpha$ [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	h	W			
GIR / GIR 12 UK	23	50	19	11	24,5	0,096

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952493695
Inside diameter	12 mm
Inside diameter	0.472" inch
Outside diameter	34 mm
Outside diameter	1.339" inch
Thickness	10 mm
Thickness	0.394" inch
Type	SI
Weight	96 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE