

# SI Rod end GIL17-UK-2RS-DURBAL - GIL17-UK-2RS-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/si/gil17-uk-2rs-durbal>

## GIL17-UK-2RS



**female thread:** maintenance free, according to DIN ISO 12240-4; series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.

**Sliding combination:** steel / bronze-PTFE fabric

**Rod end body:** surface zinc plated

**Inner ring:** bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:** steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** no lubrication necessary, maintenance free

order number	d	G	B	measurement [mm]				
right hand thread	left hand thread			C <sub>1</sub>	C <sub>2</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
GIL 17 UK (-2RS)	17	M 16	14	11,0	46	24,0	30	

type	measurement [mm]			$\alpha$ [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	t <sub>3</sub> min	h	W			
GIR / GIL 17 UK	34	67	27	10	45,0	0,220

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952493770
Inside diameter	17 mm
Outside diameter	46 mm
Thickness	14 mm
Type	SI
Weight	220 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE