

SI Rod end GIR20-UK-2RS-DURBAL - GIR20-UK-2RS-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/si/gir20-uk-2rs-durbal>

GIR20-UK-2RS



female thread: maintenance free, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.

Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE fabric

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: no lubrication necessary, maintenance free

order number	measurement [mm]	
GIR 20 UK (-2RS)	d	G
	B	C ₁
	C ₂	d ₂
	d ₄	h
	G	W
	20	M 20 x 1,5
	16	13,0
	53	27,5
	35	

type	measurement [mm]			load rating	weight
	t _{3 min}	h	W	C ₀ [kN]	[kg]
GIR / GIL 20 UK	40	77	32	60,0	0,350

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952493855
Inside diameter	20 mm
Outside diameter	53 mm
Thickness	16 mm
Type	SI
Weight	350 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE