


SI Rod end GIL25-UK-2RS-DURBAL - GIL25-UK-2RS-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/si/gil25-uk-2rs-durbal>

GIL25-UK-2RS



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.



female thread: maintenance free, according to DIN ISO 12240-4; series E

Sliding combination: steel / bronze-PTFE fabric

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: no lubrication necessary, maintenance free

order number	d	G	B	C ₁	d ₂	d ₃	d ₄
GIL 25 UK (-2RS)	25	M 24 x 2	20	17,0	64	33,5	42

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	l ₃ min	h	W			
GIR / GIL 25 UK	48	94	36	7	83,0	0,640

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952493930
Inside diameter	25 mm
Outside diameter	64 mm
Thickness	20 mm
Type	SI
Weight	640 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.com
 (646) 712 9672
 CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE