

# SI Rod end GIR70-UK-2RS-DURBAL - GIR70-UK-2RS-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/si/gir70-uk-2rs-durbal>

## GIR70-UK-2RS



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4;  
series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.


**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / bronze-PTFE fabric

**Inner ring:**  
bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:**  
steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:**  
no lubrication necessary,  
maintenance free



order number	d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
GIR 70 UK-2RS	70	M 56 x 4	49	42,0	160	80,0	98

type	measurement [mm]			α [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>3</sub> min	h	W			
GIR / GIR 70 UK-2RS	80	200	85	6	610,0	8,600

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952494296
Inside diameter	70 mm
Outside diameter	160 mm
Thickness	49 mm
Type	SI
Weight	8600 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE