

## SA Rod end POS8-DURBAL - POS8-DURBAL


<https://www.123bearing.com/bearing-housing/rod-end/sa/pos8-durbal>

**POS8**



**Description:** DIN ISO rod end K series. Sliding combination steel / heavy duty bronze.

male thread, maintenance free, according to DIN ISO 12240-4, series K



**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / heavy duty bronze

**Inner ring:**  
bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:**  
heavy duty bronze with lubrication

**Lubrication:**  
lubrication required

order number	right hand thread		left hand thread		measurement [mm]		
	B	G	M	B	C <sub>1</sub>	d <sub>1</sub>	
POS 8	8	M 8		12	9,00	22	

type	measurement [mm]		α [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	h			
POS / POSL 8	25	42	14	11,6	0,030

### PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952494449
Inside diameter	8 mm
Outside diameter	22 mm
Thickness	12 mm
Type	SA
Weight	30 g
Thread	Right-hand thread
Lubrication	without
Packaging	-
Standard	No standard

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE