

SA Rod end POSL8-DURBAL - POSL8-DURBAL


<https://www.123bearing.com/bearing-housing/rod-end/sa/posl8-durbal>

POSL8



Description: DIN ISO rod end K series. Sliding combination steel / heavy duty bronze.

male thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



rod end body:
surface zinc plated

Sliding combination:
steel / heavy duty bronze

inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
heavy duty bronze with lubrication

Lubrication:
lubrication required

order number	right hand thread		left hand thread		measurement [mm]		
	B	G	M	B	C ₁	d ₁	
POSL 8	8	M 8		12	9,00	22	

type	measurement [mm]		α [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	h			
POS / POSL 8	25	42	14	11,6	0,030

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952494456
Inside diameter	8 mm
Outside diameter	22 mm
Thickness	12 mm
Type	SA
Weight	30 g
Thread	Left-hand thread
Lubrication	without
Packaging	-
Standard	No standard

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE