

## SA Rod end POSL28-DURBAL - POSL28-DURBAL


<https://www.123bearing.com/bearing-housing/rod-end/sa/posl28-durbal>

### POSL28



**Description:** DIN ISO rod end K series. Sliding combination steel / heavy duty bronze.

male thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K



**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / heavy duty bronze

**Inner ring:**  
bearing steel, hardened, ground and  
spherical surface chromium plated

**Outer ring:**  
heavy duty bronze with lubrication

**Lubrication:**  
lubrication required

order number	measurement [mm]		measurement [mm]		
	right hand thread	left hand thread	B	C <sub>1</sub>	d <sub>1</sub>
POSL 28	28	M 27 x 2	35	24,00	66

type	measurement [mm]		α [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	h			
POS / POSL 28	62	103	15	75,5	0,960

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952494814
Inside diameter	28 mm
Outside diameter	66 mm
Thickness	35 mm
Type	SA
Weight	960 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE