

SI Rod end SIZP6-S-DURBAL - SIZP6-S-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/si/sizp6-s-durbal>

SIZP6-S



Description: DIN ISO rod end K series. Dimensions in inch. Sliding combination steel / heavy duty bronze. With grease nipple.

female thread: lubrication required, similar to DIN ISO 12240-4, series K, measurement in inches

Rod end body: surface zinc plated

Sliding combination: steel / heavy duty bronze

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: heavy duty bronze with lubrication

Lubrication: lubrication required, with grease nipple

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
SIZP 6 S		6,35	1/4 - 28	9,53	7,14	19,05	9,15	11,91

type	inches	measurement [mm]		h	α [°]	load rating C ₀ [kN]	weight [kg]
SIZP / SIZPL 6 S	1 / 4 "	19,05	9,53	33,32	13	7,7	0,025

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952495668
Inside diameter	6.35 mm
Outside diameter	19.05 mm
Thickness	9.53 mm
Type	SI
Weight	25 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE