

## SI Rod end SIZPL12-S-DURBAL - SIZPL12-S-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/si/sizpl12-s-durbal>

### SIZPL12-S



**Description:** DIN ISO rod end K series. Dimensions in inch. Sliding combination steel / heavy duty bronze. With grease nipple.

**female thread:** lubrication required, similar to DIN ISO 12240-4, series K, measurement in inches

**rod end body:** surface zinc plated

**Sliding combination:** steel / heavy duty bronze

**inner ring:** bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:** heavy duty bronze with lubrication

**Lubrication:** lubrication required, with grease nipple

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
SIZPL 12 S		12,70	1/2 - 20	15,88	12,70	33,32	18,67	22,23

type	inches	measurement [mm]			α [°]	load rating C <sub>0</sub> [kN]	weight [kg]
		l <sub>1</sub> min	W	h			
SIZP / SIZPL 12 S	1 / 2 "	30,15	19,05	53,98	9	19,0	0,133

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952495811
Inside diameter	12.7 mm
Inside diameter	1/2" inch
Outside diameter	33.32 mm
Outside diameter	1.312" inch
Thickness	15.88 mm
Thickness	5/8" inch
Type	SI
Weight	133 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE