

SI Rod end SIZPL15-S-DURBAL - SIZPL15-S-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/si/sizpl15-s-durbal>

SIZPL15-S



Description: DIN ISO rod end K series. Dimensions in inch. Sliding combination steel / heavy duty bronze. With grease nipple.

female thread: lubrication required, similar to DIN ISO 12240-4, series K, measurement in inches

Rod end body: surface zinc plated

Sliding combination: steel / heavy duty bronze

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: heavy duty bronze with lubrication

Lubrication: lubrication required, with grease nipple

| order number | right hand thread | left hand thread | measurement [mm] | | | | | | |
|--------------|-------------------|------------------|------------------|-------|-------|-------|-------|--|--|
| | d | G | B | C1 | d2 | d3 | d4 | | |
| SIZPL 15 S | 15,88 | 5/8 - 18 | 19,05 | 14,27 | 38,10 | 21,84 | 25,40 | | |

| type | inches | l ₁ min | W | h | α [°] | load rating C ₀ [kN] | weight [kg] |
|-------------------|---------|--------------------|-------|-------|-------|---------------------------------|-------------|
| SIZP / SIZPL 15 S | 5 / 8 " | 38,10 | 22,23 | 63,50 | 11 | 21,0 | 0,190 |

PRODUCT FEATURES

| | |
|------------------|------------------|
| Brand | DURBAL |
| N° Ean13 | 3663952495873 |
| Inside diameter | 15.88 mm |
| Outside diameter | 38.1 mm |
| Thickness | 19.05 mm |
| Type | SI |
| Weight | 190 g |
| Thread | Left-hand thread |
| Lubrication | without |
| Packaging | 1 |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE