

SA Rod end SAZJL6-DURBAL - SAZJL6-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/sa/sazjl6-durbal>


SAZJL6



female thread:
lubrication
required,
similar to
DIN ISO 12240-4,
series K,
measurement in
inches



Description: DIN ISO rod end K series. Dimensions in inch. Housing made of forged steel, sliding combination steel / steel. Size ≥ 9 with grease nipple can be mounted upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
rod end body pressed around inner ring

Lubrication:
lubrication required

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
SAZJL 6		6,35	14 - 28	9,53	6,35	19,05
type	inches	measurement [mm]		α [°]	load rating C ₀ [kN]	weight [g]
SAZI / SAZJL 6	1 / 4 "	25,40	39,67	13,5	6,6	0,018

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952496382
Inside diameter	6.35 mm
Outside diameter	19.05 mm
Thickness	9.53 mm
Type	SA
Weight	18 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE