

SA Rod end SAZJ15-DURBAL - SAZJ15-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/sa/sazj15-durbal>


SAZJ15



female thread:
lubrication
required,
similar to
DIN ISO 12240-4,
series K,
measurement in
inches



Description: DIN ISO rod end K series. Dimensions in inch. Housing made of forged steel, sliding combination steel / steel. Size ≥ 9 with grease nipple can be mounted upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
rod end body pressed around inner ring

Lubrication:
lubrication required

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
SAZJ 15		15,88	5/8 - 18	19,05	12,29	38,10
type	inches	measurement [mm] l ₁ min	h	α [°]	load rating C ₀ [kN]	weight [kg]
SAZI / SAZJ 15	5 / 8 "	41,28	66,68	13,0	29,0	0,160

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952496580
Inside diameter	15.88 mm
Outside diameter	38.1 mm
Thickness	19.05 mm
Type	SA
Weight	160 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE