

SA Rod end SAZJL19-DURBAL - SAZJL19-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/sa/sazjl19-durbal>


SAZJL19



female thread:
lubrication
required,
similar to
DIN ISO 12240-4,
series K,
measurement in
inches



Description: DIN ISO rod end K series. Dimensions in inch. Housing made of forged steel, sliding combination steel / steel. Size ≥ 9 with grease nipple can be mounted upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
rod end body pressed around inner ring

Lubrication:
lubrication required

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
SAZJL 19		19,05	3/4 - 16	22,23	15,06	44,45
type	inches	measurement [mm] l ₁ min	h	α [°]	load rating C ₀ [kN]	weight [kg]
SAZI / SAZJL 19	3 / 4 "	44,45	73,03	12,0	44,0	0,260

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952496627
Inside diameter	19.05 mm
Outside diameter	44.45 mm
Thickness	22.23 mm
Type	SA
Weight	260 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE