

SI Rod end SIZJ4-DURBAL - SIZJ4-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/si/sizj4-durbal>

SIZJ4



female thread:
lubrication
required,
similar to
DIN ISO 12240-4,
series K,
measurement in
inches

Description: DIN ISO rod end K series. Dimensions
in inch. Sliding combination steel / steel.
Size ≥ 9 with grease nipple can be mounted upon
request.

Rod end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
rod end body pressed around inner ring

Lubrication:
lubrication required

order number	right hand thread	left hand thread	measurement [mm]						
SIZJ 4			d	B	C ₁	d ₂	G	d ₃	d ₄
			4,83	7,92	5,94	15,88	10 - 32	7,54	10,31

type	inches	h ₁ min	measurement [mm]		α	load rating	weight
SIZJ / SIZJL 4			W	h	[°]	C ₀ (KN)	[g]
		12,70	7,92	26,97	10,0	6,8	0,018

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952496665
Inside diameter	4.83 mm
Outside diameter	15.88 mm
Thickness	7.92 mm
Type	SI
Weight	18 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE