

## SI Rod end DSIZJ6-DURBAL - DSIZJ6-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/si/dsizj6-durbal>


### DSIZJ6



female thread:  
lubrication  
required,  
similar to  
DIN ISO 12240-4,  
series K,  
measurement in  
inches



**Description:** DIN ISO rod end K series. Dimensions  
in inch. Sliding combination steel / steel.  
Size  $\geq 9$  with grease nipple can be mounted upon  
request.



**Rod end body:**  
surface zinc plated  
**Sliding combination:**  
steel / steel  
**Inner ring:**  
bearing steel, hardened, ground and  
spherical surface chromium plated  
**Outer ring:**  
rod end body pressed around inner ring  
**Lubrication:**  
lubrication required

order number	right hand thread	left hand thread	measurement [mm]					
	d	B	C <sub>1</sub>	d <sub>2</sub>	G	d <sub>3</sub>	d <sub>4</sub>	
<b>DSIZJ 6</b>	6,35	9,53	6,35	19,05	1/4 - 28	9,15	11,91	
type	inches	h <sub>1</sub> min	measurement [mm]		α	load rating	weight	
			W	h	[°]	C <sub>0</sub> [kN]	[g]	
<b>DSIZJ / DSIZJL 6</b>	1 / 4 "	15,88	9,53	33,32	13,5	9,6	0,023	

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952496726
Inside diameter	6.35 mm
Inside diameter	1/4" inch
Outside diameter	19.05 mm
Outside diameter	3/4" inch
Thickness	9.53 mm
Thickness	3/8" inch
Type	SI
Weight	23 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE