

SI Rod end SIZJL12-DURBAL - SIZJL12-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/si/sizjl12-durbal>

SIZJL12



female thread:
lubrication
required,
similar to
DIN ISO 12240-4,
series K,
measurement in
inches

Description: DIN ISO rod end K series. Dimensions
in inch. Sliding combination steel / steel.
Size ≥ 9 with grease nipple can be mounted upon
request.

Rod end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
rod end body pressed around inner ring

Lubrication:
lubrication required

order number	d	B	C ₁	d ₂	G	d ₃	d ₄
SIZJL 12	12,70	15,88	11,50	33,32	1/2 - 20	18,67	22,23

type	inches	h ₁ min	measurement [mm]	h	α	load rating	weight
			W		[°]	C ₀ (KN)	[g]
SIZJ / SIZJL 12	1 / 2 "	25,40	19,05	53,98	10,0	28,0	0,132

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952496863
Inside diameter	12.7 mm
Outside diameter	33.32 mm
Thickness	15.88 mm
Type	SI
Weight	132 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE