

## SI Rod end SIZJ19-DURBAL - SIZJ19-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/si/sizj19-durbal>

### SIZJ19



**female thread:**  
lubrication  
required,  
similar to  
DIN ISO 12240-4,  
series K,  
measurement in  
inches

**Description:** DIN ISO rod end K series. Dimensions  
in inch. Sliding combination steel / steel.  
Size ≥ 9 with grease nipple can be mounted upon  
request.

**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / steel

**Inner ring:**  
bearing steel, hardened, ground and  
spherical surface chromium plated

**Outer ring:**  
rod end body pressed around inner ring

**Lubrication:**  
lubrication required

order number	d	B	C <sub>1</sub>	measurement [mm]		G	d <sub>3</sub>	d <sub>4</sub>
SIZJ 19	19,05	22,23	15,06	44,45		3/4 - 16	25,02	28,58
type	inches	h <sub>1</sub> min	measurement [mm]		h	α	load rating C <sub>0</sub> [kN]	weight [g]
SIZJ / SIZJL 19	3 / 4 "	34,93	25,40	73,03		12,0	44,0	0,295

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952496955
Inside diameter	19.05 mm
Inside diameter	3/4" inch
Outside diameter	44.45 mm
Outside diameter	1 3/4" inch
Thickness	22.23 mm
Thickness	7/8" inch
Type	SI
Weight	295 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE