

GE Rod end SIL6-E-DURBAL - SIL6-E-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/ge/sil6-e-durbal>

SIL6-E



female thread; lubrication required, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2/R5 with additional seals also available.

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

order number

right hand thread	left hand thread	measurement (mm)						
SIL 6 E		d	G	B	C ₁	d ₂	d ₃	d ₄
		6	M 6	6	4,4	21	10,0	13

measurement [mm]

type	l ₁ min	W	h	α [°]	load rating C ₀ [kN]	weight [g]
SI / SIL 6 E	11	11	30	13	8,2	0,021

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3616060467881
Inside diameter	6 mm
Outside diameter	21 mm
Thickness	6 mm
Type	GE
Weight	21 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE