

## SI Rod end SI17-ES-DURBAL - SI17-ES-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/si/si17-es-durbal>

### SI17-ES



**female thread;**  
**lubrication**  
**required,**  
**according to**  
**DIN ISO 12240-4;**  
**series E**

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGL...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSI...ES-2/R5 with additional seals also available.

**Sliding combination:**  
steel / steel

**Inner ring:**  
bearing steel, hardened, ground and phosphated

**Outer ring:**  
bearing steel, hardened, ground and phosphated

**Lubrication:**  
lubrication required

**Rod end body:**  
surface zinc plated

order number		measurement (mm)						
right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
SI 17 ES		17	M 16	14	11,0	46	24,0	30

type	measurement [mm]			$\alpha$ [°]	load rating $C_0$ [kN]	weight [g]
	$l_2$ min	W	h			
SI / SII 17 ES	34	27	67	10	45,0	0,22

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952496986
Inside diameter	17 mm
Outside diameter	46 mm
Thickness	14 mm
Type	SI
Weight	220 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE