

# SI Rod end SI25-ES-2RS-DURBAL - SI25-ES-2RS-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/si/si25-es-2rs-durbal>

## SI25-ES-2RS



**female thread; lubrication required, according to DIN ISO 12240-4; series E**

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSI...ES-2RS with additional seals also available.

**Sliding combination:** steel / steel

**Inner ring:** bearing steel, hardened, ground and phosphated

**Outer ring:** bearing steel, hardened, ground and phosphated

**Lubrication:** lubrication required

**order number**

right hand thread	left hand thread
SI 25 ES (-2RS)	

**measurement (mm)**

d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
25	M 24 x 2	20	17,0	64	33,5	42

**measurement [mm]**

type	l <sub>3</sub> min	W	h	$\alpha$ [°]	load rating C <sub>0</sub> [kN]	weight [kg]
SI / SII 25 ES (-2RS)	48	36	94	7	83,0	0,64

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952497198
Inside diameter	25 mm
Outside diameter	64 mm
Thickness	20 mm
Type	SI
Weight	640 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE