

# SI Rod end SI40-ES-2RS-DURBAL - SI40-ES-2RS-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/si/si40-es-2rs-durbal>

## SI40-ES-2RS



**female thread;**  
**lubrication**  
**required,**  
**according to**  
**DIN ISO 12240-4;**  
**series E**

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSI...ES-2RS with additional seals also available.

**Sliding combination:**  
steel / steel

**Inner ring:**  
bearing steel, hardened, ground and phosphated

**Outer ring:**  
bearing steel, hardened, ground and phosphated

**Lubrication:**  
lubrication required

**Rod end body:**  
surface zinc plated

order number		measurement (mm)						
right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
SI 40 ES (-2RS)		40	M 39 x 3	28	23,0	92	52,0	65

type	measurement [mm]			$\alpha$ [°]	load rating $C_0$ [kN]	weight [kg]
	$l_1$ min	W	h			
SI / SII 40 ES (-2RS)	65	55	142	7	180,0	2,0

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952497389
Inside diameter	40 mm
Outside diameter	92 mm
Thickness	28 mm
Type	SI
Weight	2000 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE