

SI Rod end SIL40-ES-2RS-DURBAL - SIL40-ES-2RS-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/si/sil40-es-2rs-durbal>

SIL40-ES-2RS



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

Rod end body:
surface zinc plated

| order number | | measurement (mm) | | | | | | |
|-------------------|-------------------------|------------------|----------|----|------|----|------|----|
| right hand thread | left hand thread | d | G | B | C1 | d2 | d3 | d4 |
| | SIL 40 ES (-2RS) | 40 | M 39 x 3 | 28 | 23,0 | 92 | 52,0 | 65 |

| type | measurement [mm] | | | α [°] | load rating C_0 [kN] | weight [kg] |
|-----------------------|------------------|----|-----|-----------------|------------------------------|----------------|
| | l_1 min | W | h | | | |
| SI / SIL 40 ES (-2RS) | 65 | 55 | 142 | 7 | 180,0 | 2,0 |

PRODUCT FEATURES

| | |
|------------------|------------------|
| Brand | DURBAL |
| N° Ean13 | 3663952497433 |
| Inside diameter | 40 mm |
| Outside diameter | 92 mm |
| Thickness | 28 mm |
| Type | SI |
| Weight | 2000 g |
| Thread | Left-hand thread |
| Lubrication | with |
| Packaging | 1 |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE