

## SI Rod end SI60-ES-DURBAL - SI60-ES-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/si/si60-es-durbal>

### SI60-ES



**female thread; lubrication required, according to DIN ISO 12240-4; series E**

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSI...ES-2/R5 with additional seals also available.

**Sliding combination:** steel / steel

**Inner ring:** bearing steel, hardened, ground and phosphated

**Outer ring:** bearing steel, hardened, ground and phosphated

**Lubrication:** lubrication required

**Rod end body:** surface zinc plated

order number		measurement (mm)						
right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
SI 60 ES		60	M 52 x 3	44	38,0	135	70,0	88

type	measurement [mm]				load rating $C_0$ [kN]	weight [kg]
	$l_1$ min	W	h	$\alpha$ [°]		
SI / SII 60 ES	70	75	175	6	450,0	5,5

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952497662
Inside diameter	60 mm
Outside diameter	135 mm
Thickness	44 mm
Type	SI
Weight	5500 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE