

## SI Rod end SI60-ES-2RS-DURBAL - SI60-ES-2RS-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/si/si60-es-2rs-durbal>

### SI60-ES-2RS



**female thread;**  
**lubrication**  
**required,**  
**according to**  
**DIN ISO 12240-4;**  
**series E**

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSI...ES-2RS with additional seals also available.

**Sliding combination:**  
steel / steel

**Inner ring:**  
bearing steel, hardened, ground and phosphated

**Outer ring:**  
bearing steel, hardened, ground and phosphated

**Lubrication:**  
lubrication required

**Rod end body:**  
surface zinc plated

order number		measurement (mm)						
right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
SI 60 ES (-2RS)		60	M 52 x 3	44	38,0	135	70,0	88

type	measurement [mm]				load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	W	h	α [°]		
SI / SII 60 ES (-2RS)	70	75	175	6	450,0	5,5

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952497679
Inside diameter	60 mm
Outside diameter	135 mm
Thickness	44 mm
Type	-
Weight	5500 g
Thread	-
Lubrication	-
Packaging	-
Standard	-

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE